

MLZ-KA SERIES



Indoor Unit



MLZ-KA25/35/50VA

Panel

MLP-440W

Outdoor Unit

For MXZ Connection Only



Type				Inverter Heat Pump		
Indoor Unit				MLZ-KA25VA	MLZ-KA35VA	MLZ-KA50VA
Outdoor Unit				N / A*	N / A*	N / A*
Power Supply	Source			Outdoor power supply		
	Outdoor (V/Phase/Hz)			230 / Single / 50		
Cooling	Capacity	Rated	kW	-	-	-
		Min - Max	kW	-	-	-
	Total Input	Rated	kW	-	-	-
	EER			-	-	-
		EEL Rank		-	-	-
	SPL	Indoor Unit [Lo-Mid-Hi]	dB(A)	29 - 32 - 35	31 - 34 - 37	34 - 38 - 43
		Outdoor Unit [Rated]	dB(A)	-	-	-
	Air Volume	Indoor Unit [Lo-Mid-Hi]	m³/min	7.2 - 8.0 - 8.8	7.3 - 8.4 - 9.4	8.3 - 9.8 - 11.4
		Outdoor Unit [Rated]	m³/min	-	-	-
	Heating	Capacity	Rated	kW	-	-
Min - Max			kW	-	-	-
Total Input		Rated	kW	-	-	-
COP				-	-	-
		EEL Rank		-	-	-
SPL		Indoor Unit [Lo-Mid-Hi]	dB(A)	28 - 32 - 36	31 - 35 - 38	34 - 39 - 43
		Outdoor Unit [Rated]	dB(A)	-	-	-
Air Volume		Indoor Unit [Lo-Mid-Hi]	m³/min	7.0 - 8.2 - 9.2	7.7 - 8.8 - 9.9	8.8 - 10.3 - 11.8
		Outdoor Unit [Rated]	m³/min	-	-	-
Operating Current (max)				-	-	-
Indoor Unit	Input	Rated	kW	0.040	0.040	0.040
	Operating Current (max)		A	0.4	0.4	0.4
	Dimensions	H x W x D	mm	175 - 1102 - 360	175 - 1102 - 360	175 - 1102 - 360
	Weight		kg	15	15	15
Panel	Breaker Size		A	-	-	-
	Dimensions	H x W x D	mm	34 - 1200 - 414	34 - 1200 - 414	34 - 1200 - 414
	Weight		kg	3.5	3.5	3.5
Outdoor Unit	Dimensions	H x W x D	mm	-	-	-
	Weight		kg	-	-	-
	Operating Current (max)		A	-	-	-
	Breaker Size		A	-	-	-
Ext. Piping	Diameter	Liquid / Gas	mm	6.35 / 9.52	6.35 / 9.52	6.35 / 12.7
	Max. Length	Out-In	m	-	-	-
	Max. Height	Out-In	m	-	-	-
Guaranteed Operating Range [Outdoor]		Cooling	°C	-	-	-
		Heating	°C	-	-	-

* MLZ is for MXZ connection only.