

MSZ-S SERIES



Indoor Unit



MSZ-SF15/20VA

Outdoor Unit

For MXZ Connection Only



Type				Inverter Heat Pump	
Indoor Unit				MSZ-SF15VA	MSZ-SF20VA
Outdoor Unit				N/A*2	N/A*2
Power Supply	Source	Outdoor power supply			
	Outdoor (V/Phase/Hz)	230 / Single / 50			
Cooling	Capacity	Rated	kW	-	-
		Min - Max	kW	-	-
	Total Input	Rated	kW	-	-
	EER			-	-
		EEL Rank		-	-
	SPL	Indoor Unit [Silent-Lo-Mid-Hi-SHi*1]	dB(A)	21 - 26 - 30 - 35 - 40	21 - 26 - 30 - 35 - 42
		Outdoor Unit [Rated]	dB(A)	-	-
	Air Volume	Indoor Unit [Silent-Lo-Mid-Hi-SHi*1]	m ³ /min	3.5 - 3.9 - 4.6 - 5.5 - 6.4	3.5 - 3.9 - 4.6 - 5.5 - 6.9
		Outdoor Unit [Rated]	m ³ /min	-	-
				-	-
Heating	Capacity	Rated	kW	-	-
		Min - Max	kW	-	-
	Total Input	Rated	kW	-	-
	COP			-	-
		EEL Rank		-	-
	SPL	Indoor Unit [Silent-Lo-Mid-Hi-SHi*1]	dB(A)	21 - 26 - 30 - 35 - 40	21 - 26 - 30 - 35 - 42
		Outdoor Unit [Rated]	dB(A)	-	-
	Air Volume	Indoor Unit [Silent-Lo-Mid-Hi-SHi*1]	m ³ /min	3.7 - 4.4 - 5.0 - 6.0 - 6.8	3.7 - 4.4 - 5.0 - 6.0 - 7.3
		Outdoor Unit [Rated]	m ³ /min	-	-
				-	-
Operating Current (max)				-	-
Indoor Unit	Input	Rated	kW	0.017	0.019
	Operating Current (max)		A	0.17	0.19
	Dimensions	H x W x D	mm	250 - 760 - 168	250 - 760 - 168
	Weight		kg	7.7	7.7
	Breaker Size		A	-	-
Outdoor Unit	Dimensions	H x W x D	mm	-	-
	Weight		kg	-	-
	Operating Current (max)		A	-	-
	Breaker Size		A	-	-
Ext. Piping	Diameter	Liquid / Gas	mm	6.35 / 9.52	6.35 / 9.52
	Max. Length	Out-In	m	-	-
	Max. Height	Out-In	m	-	-
Guaranteed Operating Range [Outdoor]			Cooling	°C	-
			Heating	°C	-

*1 SHi → Super High *2 MSZ-S is for MXZ connection only.